

Proposed Code Change State Form 41186R

RETURN TO: INDIANA DEPARTMENT OF HOMELAND SECURITY CODE SERVICES SECTION

302 W. Washington Street Room W246

Indianapolis, IN 46204

INSTRUCTIONS:

Only TYPED copy accepted.

FOR OFFICE USE ONLY

Received 11/17/09

Code 50.11.3.1-09

	, , , , , , , , , , , , , , , , ,	al requiring more space.	
Code Title			Edition
Indiana Residential Code			2009
Section number and title			Page
<u> </u>	Figure 703.7.5 (1)	Trul	2 of 3
Proponent		Title	
Address	uilders and Building Officials		Phone
2175 N Cullen Ave; Evansvi	ille IN 47715	Civic	
		Room 310; Evansville, IN 47708	
Change to read as follows	Add to read as follows [PROPOSED COD	Delete and substitute as follows DE CHANGE (Check One)	Delete without substitution
igure for Drained Cavit	y <u>for crawl space</u> .		
		FIGU	JRE R703.7.5(1)
		4" DD101/ NEVEED	
15# FELT OR HOUSE WRAP WITH		4" BRICK VENEER	ž
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24		4" BRICK VENEER	
MINIMUM MOISTURE VAPOR	HOURS		,
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24	HOURS	4" BRICK VENEER SHEATHING	•
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE	HOURS		
MIÑIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) ——	HOURS		
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4"	HOURS	SHEATHING	
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6)	HOURS	SHEATHING FLOOR JOIST	
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6) DRAINED CAVITY	HOURS	SHEATHING	.6)
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6)	HOURS	SHEATHING FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1	
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6) DRAINED CAVITY	HOURS	FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1 GROUTED FULL CRAWL SPAC	E
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6)	HOURS	SHEATHING FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1	E 16" DIAMETER, MAX OF 33"
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6) DRAINED CAVITY GRADE (6" MIN. BELOW SILL PLATE	HOURS	FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1 GROUTED FULL CRAWL SPAC WEEP HOLES DRILLED A MIN 3/	E 16" DIAMETER, MAX OF 33"
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6) DRAINED CAVITY	HOURS	FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1 GROUTED FULL CRAWL SPAC WEEP HOLES DRILLED A MIN 3/	E 16" DIAMETER, MAX OF 33"
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6) DRAINED CAVITY DRAINED CAVITY DRAINED CAVITY	HOURS	FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1 GROUTED FULL CRAWL SPAC WEEP HOLES DRILLED A MIN 3/ INTERVAL TO APPROVED DRAINAG OPTIONAL: OPERATIONAL MECH	E 16" DIAMETER, MAX OF 33" E SYSTEM HANICAL
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6) DRAINED CAVITY DRAINED CAVITY DRAINED CAVITY	HOURS	FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1 GROUTED FULL CRAWL SPAC WEEP HOLES DRILLED A MIN 3/ INTERVAL TO APPROVED DRAINAGE OPTIONAL: OPERATIONAL MECHOR GRAVITY DRAINAGE SYSTEM	E 16" DIAMETER, MAX OF 33" E SYSTEM HANICAL
MINIMUM MOISTURE VAPOR TRANSMISSION OF 35g/mxm/24 (TABLE 703.4) METAL TIE HOUSE WRAP EXTENDED 4" BELOW SILL PLATE (SEC.404.1.6) DRAINED CAVITY DRAINED CAVITY DRAINED CAVITY	HOURS	FLOOR JOIST 7" ANCHOR BOLT (SEC. 403.1 GROUTED FULL CRAWL SPAC WEEP HOLES DRILLED A MIN 3/ INTERVAL TO APPROVED DRAINAG OPTIONAL: OPERATIONAL MECH	E 16" DIAMETER, MAX OF 33" E SYSTEM HANICAL M R TO

REVIEW RECOMMENDATION	
Approve	
Disapprove	
Approve as amended	
Further Study	